

**General Description**


These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

BVDSS	RDSON	ID
150V	5.2mΩ	160A

**Features**

- 150V, 160A,  $R_{DS(ON)} = 5.2m\Omega$  @  $V_{GS} = 10V$
- Improved  $dv/dt$  capability
- Fast switching
- 100% EAS Guaranteed
- Green Device Available

**TO220 Pin Configuration**



**Applications**

- Networking
- Load Switch
- LED applications
- Quick Charger

**Absolute Maximum Ratings**  $T_c=25^\circ C$  unless otherwise noted

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	150	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D$	Drain Current – Continuous ( $T_c=25^\circ C$ )	160	A
	Drain Current – Continuous ( $T_c=100^\circ C$ )	102	A
$I_{DM}$	Drain Current – Pulsed <sup>1</sup>	640	A
EAS	Single Pulse Avalanche Energy <sup>2</sup>	1800	mJ
IAS	Single Pulse Avalanche Current <sup>2</sup>	60	A
$P_D$	Power Dissipation ( $T_c=25^\circ C$ )	305	W
	Power Dissipation – Derate above $25^\circ C$	2.44	W/ $^\circ C$
$T_{STG}$	Storage Temperature Range	-55 to 150	$^\circ C$
$T_J$	Operating Junction Temperature Range	-55 to 150	$^\circ C$

**Thermal Characteristics**

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	62	$^\circ C/W$
$R_{\theta JC}$	Thermal Resistance Junction to Case	---	0.41	$^\circ C/W$

**Electrical Characteristics (T<sub>J</sub>=25 °C, unless otherwise noted)**
**Off Characteristics**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	150	---	---	V
I <sub>DSS</sub>	Drain-Source Leakage Current	V <sub>DS</sub> =120V, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C	---	---	1	μA
		V <sub>DS</sub> =120V, V <sub>GS</sub> =0V, T <sub>J</sub> =85°C	---	---	10	μA
I <sub>GSS</sub>	Gate-Source Leakage Current	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V	---	---	±100	nA

**On Characteristics**

R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance <sup>3</sup>	V <sub>GS</sub> =10V, I <sub>D</sub> =30A	---	4.3	5.2	mΩ
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>GS</sub> =V <sub>DS</sub> , I <sub>D</sub> =250μA	2.5	3.5	4.5	V
g <sub>fs</sub>	Forward Transconductance	V <sub>DS</sub> =10V, I <sub>D</sub> =3A	---	15	---	S

**Dynamic and switching Characteristics<sup>3</sup>**


Q <sub>g</sub>	Total Gate Charge	V <sub>DS</sub> =75V, V <sub>GS</sub> =10V, I <sub>D</sub> =80A	---	120	180	nC
Q <sub>gs</sub>	Gate-Source Charge		---	31	45	
Q <sub>gd</sub>	Gate-Drain Charge		---	34	50	
T <sub>d(on)</sub>	Turn-On Delay Time	V <sub>DD</sub> =75V, V <sub>GS</sub> =10V, R <sub>G</sub> =6Ω I <sub>D</sub> =80A	---	30	45	ns
T <sub>r</sub>	Rise Time		---	35	55	
T <sub>d(off)</sub>	Turn-Off Delay Time		---	35	55	
T <sub>f</sub>	Fall Time		---	45	70	
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =75V, V <sub>GS</sub> =0V, F=1MHz	---	7330	11000	pF
C <sub>oss</sub>	Output Capacitance		---	680	1050	
C <sub>rss</sub>	Reverse Transfer Capacitance		---	18	30	
R <sub>g</sub>	Gate Resistance	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, F=1MHz	---	2.7	---	Ω

**Drain-Source Diode Characteristics and Maximum Ratings**


Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I <sub>S</sub>	Continuous Source Current	V <sub>G</sub> =V <sub>D</sub> =0V, Force Current	---	---	160	A
I <sub>SM</sub>	Pulsed Source Current		---	---	320	A
V <sub>SD</sub>	Diode Forward Voltage	V <sub>GS</sub> =0V, I <sub>S</sub> =1A, T <sub>J</sub> =25°C	---	---	1	V
t <sub>rr</sub>	Reverse Recovery Time <sup>3</sup>	V <sub>R</sub> =100V, I <sub>S</sub> =20A	---	110	---	ns
Q <sub>rr</sub>	Reverse Recovery Charge <sup>3</sup>	di/dt=100A/μs, T <sub>J</sub> =25°C	---	520	---	nC

Note :


1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V<sub>DD</sub>=50V, V<sub>GS</sub>=10V, L=1mH, I<sub>AS</sub>=60A., R<sub>G</sub>=25Ω, Starting T<sub>J</sub>=25°C..
3. Essentially independent of operating temperature.




**Fig.1 Typical Output Characteristics**




**Fig.2 Continuous Drain Current vs. T<sub>c</sub>**




**Fig.3 Normalized R<sub>DS(on)</sub> vs. T<sub>j</sub>**




**Fig.4 Normalized V<sub>th</sub> vs. T<sub>j</sub>**




**Fig.5 Turn-On Resistance vs. V<sub>GS</sub>**




**Fig.6 Turn-On Resistance vs. I<sub>D</sub>**




**Fig.7 Capacitance Characteristics**




**Fig.8 Gate Charge Characteristics**




**Fig.9 Normalized Transient Impedance**



**Fig.10 Maximum Safe Operation Area**




**Fig.11 Switching Time Waveform**



**Fig.12 EAS Waveform**

## TO220 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	10.400	9.700	0.409	0.382
A1	8.900	7.400	0.350	0.291
A2	1.400	0.800	0.055	0.031
B	16.500	14.500	0.650	0.571
C	4.750	4.200	0.187	0.165
C1	1.500	1.100	0.059	0.043
D	1.000	0.600	0.039	0.024
E	4.000	3.300	0.157	0.130
E1	3.800	3.400	0.150	0.134
G	9.400	8.400	0.370	0.331
H	0.600	0.200	0.024	0.008
H1	6.850	6.200	0.270	0.244
K	2.850	2.100	0.112	0.083
L	14.000	12.500	0.551	0.492
L1	4.000	2.700	0.157	0.106
M	1.750	1.100	0.069	0.043
N	2.640	2.440	0.104	0.096