30V Dual N Channel MOSFETs

PDEV3520Z

General Description

These dual N Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

BVDSS	RDSON	ID
30V	550mΩ	800mA

Features

- *Fast switching*
- *Green Device Available*
- *Suit for 1.5V Gate Drive Applications*

SOT363 Dual Pin Configuration



Applications

- *Notebook*
- *Load Switch*
- *Networking*
- *Hand-held Instruments*

Absolute Maximum Ratings Tc=25℃ unless otherwise noted

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	±12	V
I_D	Drain Current – Continuous (T_A=25℃)	800	mA
	Drain Current – Continuous (T_A=70℃)	640	mA
I_{DM}	Drain Current – Pulsed[1]	3.2	A
P_D	Power Dissipation (T_A=25℃)	275	mW
	Power Dissipation – Derate above 25℃	2.2	mW/℃
T_{STG}	Storage Temperature Range	-55 to 150	℃
T_J	Operating Junction Temperature Range	-55 to 150	℃

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	450	℃/W

Electrical Characteristics (T_J=25 ℃, unless otherwise) noted)

Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V , I_D=250μA	30	---	---	V
$\triangle BV_{DSS}/\triangle T_J$	BV_{DSS} Temperature Coefficient	Reference to 25℃ , I_D=1mA	---	0.01	---	V/℃
I_{DSS}	Drain-Source Leakage Current	V_{DS}=30V , V_{GS}=0V , T_J=25℃	---	---	1	μA
		V_{DS}=24V , V_{GS}=0V , T_J=125℃	---	---	10	μA
I_{GSS}	Gate-Source Leakage Current	V_{GS}=±12V , V_{DS}=0V	---	---	±20	μA

On Characteristics

$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=4.5V , I_D=0.3A	---	370	550	mΩ
		V_{GS}=2.5V , I_D=0.2A	---	510	750	
$V_{GS(th)}$	Gate Threshold Voltage	V_{GS}=V_{DS} , I_D =250μA	0.5	0.7	1.2	V
$\triangle V_{GS(th)}$	$V_{GS(th)}$ Temperature Coefficient		---	-1.74	---	mV/℃
gfs	Forward Transconductance	V_{DS}=4V , I_D=0.3A	---	0.8	---	S

Dynamic and switching Characteristics

Q_g	Total Gate Charge[2,3]	V_{DS}=15V , V_{GS}=4.5V , I_D=0.3A	---	2.6	5.2	nC
Q_{gs}	Gate-Source Charge[2,3]		---	0.9	1.8	
Q_{gd}	Gate-Drain Charge[2,3]		---	0.6	1.2	
$T_{d(on)}$	Turn-On Delay Time[2,3]	V_{DD}=15V , V_{GS}=4.5V , R_G=10Ω , I_D=0.3A	---	5.5	11	ns
T_r	Rise Time[2,3]		---	4	8	
$T_{d(off)}$	Turn-Off Delay Time[2,3]		---	14.5	29	
T_f	Fall Time[2,3]		---	6.5	13	
C_{iss}	Input Capacitance	V_{DS}=15V , V_{GS}=0V , F=1MHz	---	72.9	146	pF
C_{oss}	Output Capacitance		---	18.3	36.6	
C_{rss}	Reverse Transfer Capacitance		---	7.4	14.8	

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current	V_G=V_D=0V , Force Current	---	---	0.8	A
I_{SM}	Pulsed Source Current		---	---	1.6	A
V_{SD}	Diode Forward Voltage	V_{GS}=0V , I_S=0.3A , T_J=25℃	---	---	1	V

Note :
1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed , pulse width ≦ 300μs , duty cycle ≦ 2%.
3. Essentially independent of operating temperature.



Fig.1 Continuous Drain Current vs. T_C



Fig.2 Normalized RDSON vs. T_J



Fig.3 Normalized Vth vs. T_J



Fig.4 Gate Charge Waveform



Fig.5 Normalized Transient Impedance



Fig.6 Maximum Safe Operation Area



Fig.7 Typical Output Characteristics



Fig.8 Turn-On Resistance vs. ID

SOT363 Dual PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	1.100	0.800	0.043	0.031
A1	0.100	0.000	0.004	0.000
A2	1.000	0.800	0.039	0.031
b	0.350	0.100	0.013	0.004
c	0.250	0.080	0.010	0.003
D	2.200	1.800	0.087	0.071
E	1.350	1.150	0.053	0.045
E1	2.450	1.800	0.096	0.071
e	0.65BSC		0.026BSC	
L1	0.460	0.100	0.018	0.004

SOT363 RECOMMENDED LAND PATTERN



unit : mm